

Proceedings of Women in Academia, Research and Management for Work-life Initiatives for Sustainable Health & Empowering Safety (WARM-WISHES 2026)

Bioconversion of Lignocellulosic Waste to Bioethanol: Role of Microorganisms

Sanchita Singh

Amity Institute of Biotechnology, Amity University Uttar Pradesh, Lucknow Campus, Lucknow-226028, India

Garima Awasthi*

Amity Institute of Biotechnology, Amity University Uttar Pradesh, Lucknow Campus, Lucknow-226028, India

*Corresponding Author

Dr. Garima Awasthi

Amity Institute of Biotechnology,
Amity University Uttar Pradesh (AUUP), Lucknow Campus,
Lucknow, Uttar Pradesh, India.

Email: gawasthi@lko.amity.edu

Received: 08 Aug 2026 | Received Revised Version: 22 Aug 2026 | Accepted: 09 Sep 2026 | Published: 27 Sep 2026

DOI: 10.37547/tajas/warm-33

Abstract

Lignocellulosic biomass is an abundant, renewable, and sustainable resource with significant potential for bioethanol production. However, its complex structure, composed of cellulose, hemicellulose, and lignin, presents a major challenge for its efficient conversion to fermentable sugars. The bioconversion of lignocellulosic biomass involves sequential steps such as pretreatment, enzymatic hydrolysis, and microbial fermentation, in which microorganisms play a crucial role. Bacteria and fungi are responsible for biomass degradation by producing cellulolytic enzymes, while yeasts are responsible for ethanol fermentation. Further, microbial consortia enhance the efficiency of this process through synergistic interactions. Recent advancements in enzymatic systems and bioprocessing strategies, such as simultaneous saccharification and fermentation (SSF) and consolidated bioprocessing (CBP), have significantly improved the efficiency of conversion of lignocellulosic biomass into ethanol and reduced operational costs. Additionally, genetic and metabolic engineering approaches have enabled the development of strong microbial strains capable of utilizing both hexose and pentose sugars. Several challenges still persist despite the advancements, including lignin recalcitrance, enzyme cost, and the formation of inhibitory compounds during pretreatment. Overall, continued progress in microbial engineering, enzyme optimization, and integrated bioprocessing technologies is essential to enhance efficiency, reduce costs, and achieve suitable large-scale production of lignocellulosic bioethanol.

Keywords: Lignocellulosic biomass; Bioethanol; Bioconversion; Microorganism; Enzymatic hydrolysis; Fermentation.

© 2026 Sanchita Singh, Garima Awasthi, this work is licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0). The authors retain copyright and allow others to share, adapt, or redistribute the work with proper attribution.

Cite This Article: Singh, S., & Awasthi, G. (2026). Bioconversion of Lignocellulosic Waste to Bioethanol: Role of Microorganisms. The American Journal of Applied Sciences, 382–390. <https://doi.org/10.37547/tajas/warm-33>

1. Introduction

Growing population, industrialization and urbanization have led to a great dependence on fossil fuels such as coal, crude oil and natural gas, due to the rapid rise in global consumption. However, excessive use of non-renewable energy sources has resulted in extreme environmental issues, including greenhouse emission, global warming and climate change. In addition, the depleting fossil fuel reserves and the volatility of the crude oil prices has led to the unmet need of renewable and sustainable energy sources (Balat, 2011; Nigam & Singh, 2011). Bioethanol is one of the potential biofuels, which are growing more attractive as they are renewable, biodegradable and blend well with the existing fuels (Sanchez & Cardona, 2008).

Bioethanol is produced in different generations based on the raw materials. The first-generation bioethanol produced from food crops such as corn and sugarcane hence triggering food security and land use issue. Second-generation bioethanol produced from lignocellulosic biomass (LCB) is more ideal as it is produced from non-food feedstock like agricultural wastes, forest residues, and industrial residues (Usman et al., 2026; Gayathri & Nair, 2023; Kim & Dale, 2004).

Lignocellulosic biomass is made up of many cheap and readily available feedstocks and thus an excellent feedstock to be used in large scale production of bioethanol. Moreover, its use results in the waste management and reduced pollution. The lignocellulosic biomass which comprises of major components of cellulose, hemicellulose, lignin is tightly bound to give a complex and resistant structure. The crystalline nature of cellulose provides strength, the hemicellulose is a matrix and the lignin is a protective layer which limits the access of enzymes (Mosier et al., 2005; Himmel et al., 2007). This complex structure is one of the major challenges in biomass conversion as it limits the efficient hydrolysis of the polysaccharide forming the fermentable sugars and may lead to the formation of the inhibitory compounds in biomass processing.

To overcome the above issues, microbial bioconversion has emerged as a key concern as an efficient and environmentally friendly approach. Microorganisms play a vital role in all processing steps of bioethanol, that is, pretreatment, enzyme hydrolysis and fermentation. They produce a wide range of enzymes such as cellulases, hemicellulases and lignin which help in the

breakdown of bulk biomass into sugars (Balat, 2011; Nigam & Singh, 2011). The main microorganisms used in biomass degradation are bacteria and fungi, while the fermentation is carried out by yeasts.

Lignocellulosic biomass conversion to bioethanol involves three major steps; pretreatment (disrupting the structure of the lignin and making the substrates more accessible for enzyme hydrolysis) enzyme hydrolysis (breaking down or splitting the polysaccharides into fermentable sugars) and fermentation (conversion of fermentable sugars to ethanol). More efficient bioprocesses to date such as simultaneous saccharification and fermentation and consolidated bioprocessing also improves the efficiency of the process and reduce operation costs (Taherzadeh & Karimi, 2008; Alvira et al., 2010; Galbe & Zacchi, 2007; Humbird, 2011; Wyman, 1999; Lynd et al., 2005).

Likewise, microbial consortia, GEM and metabolic engineering approaches have also been proven to be efficient as different species communicate and interact synergistically with each other. The innovative processes of rapid growth of efficient microbial systems and efficient bioconversion to develop cost effective bioethanol production are important. So, it is imperative to understand the complexity of the lignocellulosic biomass for effective bioconversion.

2. The Composition of Lignocellulosic Biomass

Lignocellulosic biomass is a complex and diverse substance and mainly consists of cellulose, hemicellulose and lignin. Cellulose is a homopolymer of β -1,4-linked glucose molecules that forms highly-ordered crystalline microfibrils and is difficult to hydrolyze by enzymes (Balat, 2011; Lynd et al., 2002).

Hemicellulose is an amorphous and branched heteropolymer in the form of different sugars including xylose, mannose and arabinose, which is biodegradable to a greater extent (Sun & Cheng, 2002).

Lignin is a hydrophilic aromatic polymer, which provides rigidity and protects to structure and thus limits access of enzymes to the polysaccharides (Mosier et al., 2005). All of these complexities make biomass recalcitrant and hard to be efficiently converted into desired products. Lignocellulosic biomass of different origins varies in composition as represented in table 1.

Table 1: Lignocellulose composition from multiple sources based on dry weight (Sun & Cheng, 2002)

Source of lignocellulose	Cellulose (%)	Hemicellulose (%)	Lignin (%)
Cotton seed hairs	80-90%	5-20%	0
Paper	85-99%	0	0-15%
Waste papers	60-70%	10-20%	5-10%
Softwood stems	45-50%	25-35%	25-35%
Hardwoods stems	40-55%	24-40%	18-25%
Newspaper	40-55%	25-40%	18-30%
Corn cobs	45%	35%	15%
Wheat straw	30%	50%	15%
Primary wastewater solids	8-15%	0	24-29%

3. Role of Microorganisms

3.1 Lignocellulosic Biomass Biodegradation

Biodegradation of lignocellulosic biomass is a multi-step process, which is mainly performed by microorganisms that produce extracellular enzymes. Lignocellulosic biomass is a complex structure made up of cellulose, hemicellulose and lignin, which are closely associated and hence recalcitrant and difficult to degrade (Mosier et al., 2005; Himmel et al., 2007). Bacteria and fungi are key in overcoming this architecture by secretion of a wide array of lignin-degrading and cellulose-degrading enzymes.

White-rot fungi are the most effective lignin degraders because they can produce oxidative enzymes such as laccase, lignin peroxidase and manganese peroxidase. These enzymes cleave the aromatic structure of lignin into lower molecular weight phenolic compounds, thus enhancing the degradation of cellulose and hemicellulose (Balat, 2011; Ragauskas et al., 2006; Singh et al., 2010; Kuhad et al., 2011). On the other hand, brown-rot fungi primarily degrades cellulose and hemicellulose and modify lignin, while soft-rot fungi play a role in certain environments.

Bacteria also play an important role in the degradation of lignocellulose, particularly in a range of environments. Bacteria like *Cellulomonas*, *Bacillus* and *Pseudomonas* secrete cellulases and hemicellulose to degrade cellulose and hemicellulose to sugars (Nigam & Singh, 2011; Rogers et al., 2007). While bacteria are less effective than fungi in degrading lignin, some genera like *Rhodococcus* and *Streptomyces* have ligninolytic enzymes.

Cellulases degrade cellulose into glucose through the combined action of endoglucanases, exoglucanases and β -glucosidases (Juturu & Wu, 2014; Zhang, 2008). Likewise, hemicellulases (such as xylanases) break down hemicellulose into pentose sugars. The recent identification of enzymes such as lytic polysaccharide monooxygenases (LPMOs) has also improved the effectiveness of biomass degradation, primarily via an oxidative pathway (Horn et al., 2012).

In conclusion, microbial biodegradation plays an important role in lignocellulosic bioconversion as it converts biomass into sugars that can be used for bioethanol production. The sugars released by the microorganisms are then used for bioethanol production.

3.2 Enzymatic System

A plethora of enzymes produced by microorganisms are involved in the degradation of lignocellulosic biomass in a concerted effort of converting structural polymers into sugars. Lignin is predominantly degraded by ligninolytic enzymes, such as laccase, lignin peroxidase and manganese peroxidase (Ragauskas et al., 2006; Yang & Wyman, 2008).

Cellulolytic enzymes play an important role in the conversion of cellulose to glucose. This is accomplished by the enzyme's endoglucanases, which break the internal bonds between the cellulose chains, exogenous glucanases which cleave cellobiose units and β -glucosidases which break cellobiose down to glucose (Juturu & Wu, 2014; Zhang, 2008).

Xylanases and β -xylosidases of hemicellulolytic enzymes will convert hemicellulose to pentose sugars xylose. Also, the recently discovered enzymes such as lytic polysaccharide monooxygenases (LPMOs) will help to breakdown biomass by oxidative cleavage with high potential to enhance the hydrolysis process (Horn et al., 2012).

3.3 Bioethanol Production

Lignocellulosic biomass is converted to bioethanol through microbial fermentation of sugars obtained from enzymatic hydrolysis. This step is crucial in the bioconversion process of microorganisms converting fermentable sugars into ethanol in controlled environments. This step is highly dependent on the microorganism used and its fermentation capacities.

Ethanol is typically produced using yeasts, with *Saccharomyces cerevisiae* being the most common because of its high ethanol yield, ethanol tolerance, and stress tolerance (Lin & Tanaka, 2006). But *S. cerevisiae* mainly metabolises hexose sugars (glucose) and is not efficient in fermenting pentose sugars (xylose) present in hemicellulose. To broaden the range of fermentable sugars, non-conventional yeasts like *Pichia stipitis* and *Candida shehatae* have been investigated for their pentose fermenting ability (Hahn-Hägerdal et al., 2007; Zaldivar et al., 2001).

Some bacteria including *Zymomonas mobilis* have also been considered as potential ethanol producers due to their high ethanol productivity and different metabolic

route (Entner–Doudoroff pathway) that leads to a higher ethanol yield and a reduced biomass yield (Rogers et al., 2007). But they have a narrow substrate specificity, limiting their use in lignocellulosic systems.

Recent studies on genetic and metabolic engineering have allowed the construction of recombinant microorganisms to ferment both pentose and hexose sugars, enhancing ethanol yield and efficiency (Stephanopoulos, 2007; Wang et al., 2024). Moreover, approaches like simultaneous saccharification and fermentation (SSF) have been used to overcome product inhibition and enhance the conversion yield (Humbird, 2011; Wyman, 1999).

However, there are still many challenges with regards to inhibitor toxicity, low efficiency of mixed sugars fermentation, and process optimization. However, ongoing improvements in microbial strain development and fermentation processes will improve the potential for industrial production of lignocellulosic bioethanol.

4. Bioconversion Pathway

Bioconversion process involves the integrated steps of converting the pre-treated biomass into ethanol by enzymes and microbes. The initial step is the pretreatment that involves disorganising the rigid lignin structure, crystallinity of cellulose and increasing the surface area of biomass, and thus, accessibility of enzymes. Physical, chemical, physico-chemical and biological pretreatments are used, however, biological pretreatment is more eco-friendly but slow compared to the other type of pretreatments (Kumar et al., 2008; Taherzadeh & Karimi, 2008; Alvira et al., 2010; Galbe & Zacchi, 2007). The next step is the enzymatic hydrolysis which involves enzymes, cellulases and hemicellulases to convert the cellulose and hemicellulose to fermentable sugars such as glucose and xylose through enzyme synergies (Juturu & Wu, 2014; Demain et al., 2005). Finally, ethanol is produced by microorganisms using sugars as a substrate. While the hexose sugars are easily fermented to ethanol, pentose sugars can be fermented to ethanol efficiently only by certain microorganisms or genetically engineered ones, and these reduce the yield of ethanol (Lin & Tanaka, 2006; Hahn-Hägerdal et al., 2007). The entire bioconversion process of lignocellulosic biomass to bioethanol is shown in Figure 1.




Figure 1: Flowchart of Bioconversion of Lignocellulosic Biomass to Bioethanol

5. Advanced Microbial and Bioprocessing Strategies

To address the challenges associated with traditional lignocellulosic bioconversion, a number of microbial and bioprocessing technologies have been explored to increase efficiency, cost-effectiveness and ethanol production.

5.1 Microbial Consortia-Based Systems

Microbial consortia are synergistic systems where various microorganisms work together to perform different functions (lignin degradation, cellulose hydrolysis, and fermentation). It improves enzyme specificity, substrate conversion and process robustness. Consortia-Based systems are especially beneficial for the processing of complex lignocellulosic feedstocks and have demonstrated better ethanol production than pure cultures (Nigam & Singh, 2011; Lynd et al., 2008).

5.2 Simultaneous Saccharification and Fermentation (SSF)

SSF combines the enzymatic hydrolysis and fermentation steps, eliminating the inhibitory effect of glucose buildup. This process increases the efficiency, reduces the risk of contamination and the cost of the process. But it is difficult to maintain the balance between optimal conditions for enzyme activity and microbial growth due to different temperature and pH requirements (Humbird, 2011; Wyman, 1999).

5.3 Consolidated Bioprocessing (CBP)

CBP is a next-generation approach where the enzymes are produced, and the biomass is hydrolysed and fermented all in one step by one organism or a consortium of organisms. This process eliminates the need to add enzymes, which is costly. But the development of efficient microorganisms that can carry out these processes is still a challenge (Lynd et al., 2005; Li et al., 2021).

5.4 Genetic and Metabolic Engineering

Metabolic and genetic engineering have greatly improved the production of lignocellulosic bioethanol. Genetically engineered microbes are tailored to enhance enzyme synthesis, tolerance to inhibitors and ethanol, as well as to ferment hexose and pentose sugars. Synthetic biology has also enabled the creation of resilient microbial strains with enhanced metabolic pathways to produce more ethanol. But there are issues with genetic stability and scale-up (Dien et al., 2003; Stephanopoulos, 2007; Wang et al., 2024).

6. Factors Influencing Bioconversion Efficiency

6.1 Physicochemical Factors

Physicochemical factors such as temperature, pH, moisture content can play a critical role in the activity of the enzyme and the growth of the microorganisms of the enzyme during lignocellulosic bioconversion.

Cellulolytic enzymes generally work optimally at temperatures of 40-50 deg C, and at slightly acidic pH (4-5). These optimal conditions can denature the enzyme and its catalytic activity. Moisture content is also important, in which insufficient moisture will stop the microbial growth, while high moisture can affect the porosity of substrate and the oxygen uptake, and therefore the effectiveness of the whole process (Roy, 2021).

6.2 Nutritional Factors

The nutritional status, particularly the carbon and nitrogen (C/N) ratio, plays an important role in the microbial growth and enzyme production. An adequate C/N ratio will ensure the proper microbial metabolism and thus increased production of the enzymes needed for biomass degradation. The absence of essential nutrients (nitrogen, phosphorus and trace nutrients) may hinder microbial activity and on the other hand, the excess of nutrients can lead to the unwanted growth of microorganism and the decreased ethanol yield (Nigam & Singh, 2011; Sarkar et al., 2012).

6.3 Availability of Oxygen

Oxygen availability is one of the key factors that determine the metabolic pathways taken by microorganisms in ethanol production. Normally, microorganisms growth and enzymes production are encouraged in aerobic environments particularly during the pretreatment and hydrolysis stages. On the other hand, ethanol fermentation is favoured under anaerobic conditions as sugar conversion to ethanol, but not to biomass and other by-products, is encouraged. Facultative microorganisms can survive in both conditions, that provides the process with flexibility (Nigam & Singh, 2011; Wingren et al., 2003).

6.4 Characteristics of Substrate

The physical and chemical properties of lignocellulosic biomass (particle size, crystallinity, lignin content and surface area) affect the efficiency of the enzymatic hydrolysis. Decreasing the particle size increases the surface area and enzyme-substrate contact. But in the presence of high lignin content, the lignin acts as a physical barrier preventing the enzyme activity and also adsorbs the enzymes. That is why proper pretreatment is required to modify the properties of the substrates and improve the bioconversion process (Olofsson et al., 2008).

7. Critical Analysis of Lignocellulosic Bioethanol Production

Despite being an environmental-friendly alternative to fossil fuels, lignocellulosic bioethanol production still faces major technical and economic barriers towards commercialization. One such constraint is the resistant nature of lignocellulosic biomass, mainly caused by lignin, which limits enzyme accessibility and the effectiveness of enzymatic hydrolysis (Mosier et al., 2005; Himmel et al., 2007). Existing pretreatment technologies enhance biomass digestibility but are often energy-intensive and can generate inhibitory compounds, thus complicating and increasing the cost of the process (Taherzadeh & Karimi, 2008; Alvira et al., 2010; Galbe & Zacchi, 2007).

The other major issue is the cost and efficiency of the enzymes used for hydrolysis. Inhibition of enzymes by reaction by-products (glucose and cellobiose) also lowers the conversion yield, further diminishing its economic feasibility (Taherzadeh & Karimi, 2008; Zhao et al., 2012). While improvements such as enzyme engineering and recycling have been suggested, they are not readily applicable in industry.

Pretreatment results in the production of inhibitors, such as furfural and hydroxy methyl furfural (HMF), and phenolic compounds that have adverse effects on microbial activity and ethanol yields (Sanchez & Cardona, 2008; Gnansounou & Dauriat, 2011). Although detoxification strategies are viable, they increase processing costs and steps, therefore making microbial strains that are tolerant to inhibitors desirable.

Additionally, the poor fermentability of pentose sugars by traditional microorganisms like *Saccharomyces cerevisiae* leads to waste of substrate and reduced ethanol production (Lin & Tanaka, 2006; Hahn-Hägerdal et al., 2007). While genetically modified strains and non-conventional yeasts have been explored, they are still unstable, difficult to scale up and perform poorly in industrial settings (Stephanopoulos, 2007).

In the aspect of process strategy, novel technologies like simultaneous saccharification and fermentation (SSF) and consolidated bioprocessing (CBP) have great potential to reduce the cost and enhance the productivity. But SSF has difficulties in achieving optimal conditions for enzymes and microorganisms, while CBP needs development of microorganisms that can perform multiple functions, which is currently being investigated

(Humbird, 2011; Wyman, 1999; Lynd et al., 2005; Li et al., 2021).

In summary, although considerable advancements have been achieved in lignocellulosic bioethanol production, the combination of effective pre-treatment, low-cost enzymes and efficient microorganisms, as well as process strategies, is crucial. Overcoming these challenges through integrated approaches such as synthetic biology, metabolic engineering and process optimisation will play a key role in the commercialisation of bioethanol at an industrial scale.

8. Future Perspectives

Future research and development of the lignocellulosic bioethanol need to be focused on efficiency improvement, cost reduction and large scale commercialization. The recent development of genetically engineered microorganisms that can ferment both hexose and pentose sugars with tolerance of inhibitors and ethanol will greatly improve the fermentation efficiency. Similarly, studies on enzyme engineering and discovery of new enzymes with improved characteristics will reduce the enzymes load and cost. Microbial consortia and synthetic biology approaches offer a possibility to integrate various stages of biomass conversion in one system.

In addition, the optimization of the pretreatment technologies to produce the least inhibitors and energy consumption is still studied. Lignocellulosic bioethanol production is a possibility and can be integrated with biorefineries to improve the energy balance and the economic feasibility (due to byproducts). Overall, multi-disciplinary advances will be of great importance in converting bioethanol into a sustainable energy source (Gourlay et al., 2012; Jørgensen et al., 2007; Adsul, 2011).

9. Conclusion

The bioconversion of the lignocellulosic biomass for bioethanol production is a sustainable and renewable source of energy that can be used as an alternative to the naturally occurring fossil fuels. Microorganisms play an important role in this process due to the effective pretreatment, enzyme hydrolysis and fermentation using different enzyme systems. Increased biomass degradation and ethanol production is achieved by bacteria, fungi, yeasts and microbial consortia. However, problems such as the recalcitrance of lignin and the cost

and efficiency of the enzyme and process still do not permit commercial scale-up. The solution to the above problems is provided by the economic growth in genetic engineering and integrated bioprocessing methods. The progress in the area will be important for sustainable and viable industrial production of bioethanol.

Author Declaration Statements

Declaration: The authors hereby declare that the manuscript submitted for consideration is an

original work and has not been published or submitted elsewhere for publication. The authors

take full responsibility for the integrity, accuracy, and ethical compliance of the work presented

in the manuscript.

Conflict of Interest: All authors confirm that:

Any potential conflicts of interest, whether financial or non-financial, have been fully disclosed. - Not Applicable

All sources of funding and financial support received for the conduct of the study have been appropriately acknowledged. – Not Applicable

Necessary ethical approvals have been obtained from the relevant institutional or regulatory bodies for studies involving human participants, animals, or sensitive data, wherever applicable. – Not Applicable

Reference

1. Balat, M. (2011). Production of bioethanol from lignocellulosic materials via the biochemical pathway: a review. *Energy conversion and management*, 52(2), 858-875.
2. Nigam, P. S., & Singh, A. (2011). Production of liquid biofuels from renewable resources. *Progress in energy and combustion science*, 37(1), 52-68.
3. Sanchez, O. J., & Cardona, C. A. (2008). Trends in biotechnological production of fuel ethanol from different feedstocks. *Bioresource technology*, 99(13), 5270-5295.
4. Usman, M., Nadeem, F., Ramzan, H., & Tahir, N. (2026). Role of nanomaterials for effective lignocellulosic biomass wastes conversion to

- hydrogen: a biorefinery perspective on commercialization and sustainability, challenges, and prospects. *Frontiers in Microbiology*, 17, 1793416.
5. Gayathri, L. N., & Nair, P. (2023). Role of Aerobic and Anaerobic Bacteria in the Bio-conversion of Lignocellulose waste material. *Journal of Microbes and Research*, 2(1), 2836-2187.
 6. Kim, S., & Dale, B. E. (2004). Global potential bioethanol production from wasted crops and crop residues. *Biomass and bioenergy*, 26(4), 361-375.
 7. Mosier, N., Wyman, C., Dale, B., Elander, R., Lee, Y. Y., Holtzapple, M., & Ladisch, M. (2005). Features of promising technologies for pretreatment of lignocellulosic biomass. *Bioresource technology*, 96(6), 673-686.
 8. Himmel, M. E., Ding, S. Y., Johnson, D. K., Adney, W. S., Nimlos, M. R., Brady, J. W., & Foust, T. D. (2007). Biomass recalcitrance: engineering plants and enzymes for biofuels production. *science*, 315(5813), 804-807.
 9. Lynd, L. R., Weimer, P. J., Van Zyl, W. H., & Pretorius, I. S. (2002). Microbial cellulose utilization: fundamentals and biotechnology. *Microbiology and molecular biology reviews*, 66(3), 506-577.
 10. Sun, Y., & Cheng, J. (2002). Hydrolysis of lignocellulosic materials for ethanol production: a review. *Bioresource technology*, 83(1), 1-11.
 11. Kumar, R., Singh, S., & Singh, O. V. (2008). Bioconversion of lignocellulosic biomass: biochemical and molecular perspectives. *Journal of industrial microbiology and biotechnology*, 35(5), 377-391.
 12. Taherzadeh, M. J., & Karimi, K. (2008). Pretreatment of lignocellulosic wastes to improve ethanol and biogas production: a review. *International journal of molecular sciences*, 9(9), 1621-1651.
 13. Alvira, P., Tomás-Pejó, E., Ballesteros, M., & Negro, M. J. (2010). Pretreatment technologies for an efficient bioethanol production process based on enzymatic hydrolysis: a review. *Bioresource technology*, 101(13), 4851-4861.
 14. Galbe, M., & Zacchi, G. (2007). Pretreatment of lignocellulosic materials for efficient bioethanol production. *Biofuels*, 41-65.
 15. Juturu, V., & Wu, J. C. (2014). Microbial cellulases: Engineering, production and applications. *Renewable and sustainable energy reviews*, 33, 188-203.
 16. Demain, A. L., Newcomb, M., & Wu, J. D. (2005). Cellulase, clostridia, and ethanol. *Microbiology and molecular biology reviews*, 69(1), 124-154.
 17. Lin, Y., & Tanaka, S. (2006). Ethanol fermentation from biomass resources: current state and prospects. *Applied microbiology and biotechnology*, 69(6), 627-642.
 18. Hahn-Hägerdal, B., Karhumäa, K., Fonseca, C., Spencer-Martins, I., & Gorwa-Grauslund, M. F. (2007). Towards industrial pentose-fermenting yeast strains. *Applied microbiology and biotechnology*, 74(5), 937-953.
 19. Rogers, P. L., Jeon, Y. J., Lee, K. J., & Lawford, H. G. (2007). *Zymomonas mobilis* for fuel ethanol and higher value products. *Biofuels*, 263-288.
 20. Dien, B. S., Cotta, M. A., & Jeffries, T. (2003). Bacteria engineered for fuel ethanol production: current status. *Applied microbiology and biotechnology*, 63(3), 258-266.
 21. Ragauskas, A. J., Williams, C. K., Davison, B. H., Britovsek, G., Cairney, J., Eckert, C. A., ... & Tschaplinski, T. (2006). The path forward for biofuels and biomaterials. *science*, 311(5760), 484-489.
 22. Singh, A., Pant, D., Korres, N. E., Nizami, A. S., Prasad, S., & Murphy, J. D. (2010). Key issues in life cycle assessment of ethanol production from lignocellulosic biomass: challenges and perspectives. *Bioresource technology*, 101(13), 5003-5012.
 23. Kuhad, R. C., Gupta, R., Khosa, Y. P., Singh, A., & Zhang, Y. H. P. (2011). Bioethanol production from pentose sugars: Current status and future prospects. *Renewable and Sustainable Energy Reviews*, 15(9), 4950-4962.

24. Zaldivar, J., Nielsen, J., & Olsson, L. (2001). Fuel ethanol production from lignocellulose: a challenge for metabolic engineering and process integration. *Applied microbiology and biotechnology*, 56(1), 17-34.
25. Lynd, L. R., Laser, M. S., Bransby, D., Dale, B. E., Davison, B., Hamilton, R., ... & Wyman, C. E. (2008). How biotech can transform biofuels. *Nature biotechnology*, 26(2), 169-172.
26. Yang, B., & Wyman, C. E. (2008). Pretreatment: the key to unlocking low-cost cellulosic ethanol. *Biofuels, Bioproducts and Biorefining: Innovation for a sustainable economy*, 2(1), 26-40.
27. Zhang, Y. P. (2008). Reviving the carbohydrate economy via multi-product lignocellulose biorefineries. *Journal of industrial microbiology and biotechnology*, 35(5), 367-375.
28. Horn, S. J., Vaaje-Kolstad, G., Westereng, B., & Eijsink, V. (2012). Novel enzymes for the degradation of cellulose. *Biotechnology for biofuels*, 5(1), 45.
29. Roy, S. (2021). *Pre-treatment methods of lignocellulosic biomass for biofuel production*. CRC Press.
30. Sarkar, N., Ghosh, S. K., Bannerjee, S., & Aikat, K. (2012). Bioethanol production from agricultural wastes: an overview. *Renewable energy*, 37(1), 19-27.
31. Wingren, A., Galbe, M., & Zacchi, G. (2003). Techno-economic evaluation of producing ethanol from softwood: Comparison of SSF and SHF and identification of bottlenecks. *Biotechnology progress*, 19(4), 1109-1117.
32. Olofsson, K., Bertilsson, M., & Lidén, G. (2008). A short review on SSF—an interesting process option for ethanol production from lignocellulosic feedstocks. *Biotechnology for biofuels*, 1(1), 7.
33. Humbird, D. (2011). Process design and economics for biochemical conversion of lignocellulosic biomass to ethanol. *Technical Report*, 40-43.
34. Wyman, C. E. (1999). Biomass ethanol: technical progress, opportunities, and commercial challenges. *Annual review of energy and the environment*, 24(1), 189-226.
35. Lynd, L. R., Van Zyl, W. H., McBride, J. E., & Laser, M. (2005). Consolidated bioprocessing of cellulosic biomass: an update. *Current opinion in biotechnology*, 16(5), 577-583.
36. Li, Y., Gao, N., Zhang, X., Zhao, G., & Song, X. (2021). Sophorolipid production using lignocellulosic biomass by co-culture of several recombinant strains of starmerella bombicola with different heterologous cellulase genes from penicillium oxalicum. *Applied biochemistry and biotechnology*, 193(2), 377-388.
37. Stephanopoulos, G. (2007). Challenges in engineering microbes for biofuels production. *Science*, 315(5813), 801-804.
38. Wang, Y., Zhang, Y., Cui, Q., Feng, Y., & Xuan, J. (2024). Composition of lignocellulose hydrolysate in different biorefinery strategies: nutrients and inhibitors. *Molecules*, 29(10), 2275.
39. Zhao X, Zhang L, Liu D. Biomass recalcitrance. *Biofuels Bioprod Bioref*. 2012;6(4):465–482.
40. Gnansounou, E., & Dauriat, A. (2011). Technoeconomic analysis of lignocellulosic ethanol. In *Biofuels* (pp. 123-148). Academic Press.
41. Gourlay, K., Arantes, V., & Saddler, J. N. (2012). Use of substructure-specific carbohydrate binding modules to track changes in cellulose accessibility and surface morphology during the amorphogenesis step of enzymatic hydrolysis. *Biotechnology for biofuels*, 5(1), 51.
42. Jørgensen, H., Kristensen, J. B., & Felby, C. (2007). Enzymatic conversion of lignocellulose into fermentable sugars: challenges and opportunities. *Biofuels, Bioproducts and Biorefining*, 1(2), 119-134.
43. Adsul, M. G. (2011). Strain improvement of penicillium janthinellum for cellulase production and biochemical characterization of xylanases from yeast.